Name: _____ **Group:** _____ **Mark:** /50 **Grade:** ____

Answer all questions

1. Read the pseudocode below and complete the trace table with the following data:

    20, 25, 4, 1, 10

    ```
    temperature = 0
    highest = 0
    lowest = 50
    total = 0
    for index = 1 to 5
        temperature = input ("Enter temperature: ")
        if temperature > highest then
            highest = temperature
        endif
        if temperature < lowest then
            lowest = temperature
        endif
        total = total + temperature
    next index
    average = total/5
    print ("Highest", highest)
    print ("Lowest", lowest)
    print ("Average", average)
    ```

Complete the trace table with the following data 20, 25, 4, 1, 10

temperature	highest	lowest	total	average	index	Output
0	0	50	0		1	

[6]

2. (a) Write pseudocode for a program which outputs the total of all the even numbers within a range entered by the user.   [5]

    (b) State **two** ways of making programs easy to understand and maintain.   [2]

3. Write a subroutine called **answerYorN** to input and check the response to a question. It should be "y" or "n". Any other response is invalid, and the function should ask the user to re-enter until a valid response is received. The value is returned by the function to the main program.

    The subroutine is called as follows:

    ```
    response = answerYorN
    ```
                                                                                          [5]

4   (a) Explain the difference between passing parameters **by value** and **by reference**.   [4]

(b) (i) What is meant by modular programming? [2]

(ii) Give **four** advantages of modular programming. [4]

(c) Explain why using local variables makes a large program easier to maintain. [2]

5. (a) When using the debugging facilities of an IDE, explain what is meant by

(i) a watch [2]

(ii) a trace [2]

(b) State **two** other features of an IDE which are useful when entering or editing program code. [2]

6. Describe briefly three(3) advantages of using subroutines in programs [6]

7. Write a pseudocode algorithm using a **for ... next** loop to read five lowercase letters and output the largest and smallest. (a is less than b). [4]

8. Write a pseudocode algorithm that asks a user for a password. They are allowed three attempts to type the correct password, which is "Tues1212".
    If they type the correct password, output "Password accepted", otherwise output "Password rejected". [4]

Total 50 marks

END OF PAPER

4